

Параметры	Наименование типового представителя								
	ОКК1-14	ОКК1-21	ОКК1-35	ОКК2-21	ОКК2-35	ОКК2-70	ОКК3-35	ОКК3-70	ОКК3-105
Диаметр обсадной колонны D , мм	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈)	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈)	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)	426 (16 ³ / ₄)	426 (16 ³ / ₄)	426 (16 ³ / ₄)
Диаметр обсадной колонны закрепляемой в подвеске D_1 , мм	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7)			219 (8 ⁵ / ₈) 219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈) 245 (9 ⁵ / ₈) 273 (10 ³ / ₄)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)	299 (11 ³ / ₄) 324 (12 ³ / ₄) 324 (12 ³ / ₄) 340 (13 ³ / ₈)
Диаметр обсадной колонны закрепляемой в подвеске D_2 , мм	–	–	–	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7) 194 (7 ³ / ₈)	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈) 273 (10 ³ / ₄)	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈) 273 (10 ³ / ₄)	219 (8 ⁵ / ₈) 245 (9 ⁵ / ₈) 273 (10 ³ / ₄)
Диаметр обсадной колонны закрепляемой в подвеске D_3 , мм	–	–	–	–	–	–	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7) 194 (7 ³ / ₈)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7) 194 (7 ³ / ₈)	140 (5 ¹ / ₂) 146 (5 ³ / ₄) 168 (6 ⁵ / ₈) 178(7) 194 (7 ³ / ₈)
Масса, кг	245...270	345...370	435...460	1115...11140	1225....1280	1540...1660	2470...2620	2470...2620	4840